

January 18, 2019

SUPPLEMENTAL / BID BULLETIN No. 2019-01

This Supplemental Bid Bulletin No. 2019-01 is being issued to advise prospective bidder/s on modifications and amendments on certain items in the Bidding Document, Invitation to Apply and Bid and Terms of Reference, if applicable for the supply and delivery of various projects:

ITB/TOR Specifications	Agreement during Pre-Bid Conference
ITB # 2019-018 Supply and Delive	ery of 5,571 vials Classical Swine Fever Vaccine
	No bidder attended
ITB # 2019-019 Supply and Delive	
Stage: Stage size: 290 x 300 mm	Supplier's request to change 232 x 230 mm End-User's considerations for this (per submitted letter to BAC Secretariat) a. A bigger stage is advantageous for the types of samples being viewed by this laboratory (i.e. insects, worms, filariae), different slides (MC Master egg-counting chamber and Neubauer slides, Microhematocrit tube viewing slide, which are larger than usual slides), More so, studying 2 slides is not possible with smaller stages, and carriers of samples (96-well microplates, petri dishes, and others). b. Need a larger stage sixe to examine different kinds of slides for comparison in one platform for ease of referencing for our Quality assurance purposes. Wider stage offers safer manipulation of samples for the laboratory staff especially for zoonotic pathogens being handled. We have proven the effectivity and efficiency of a bigger stage, thus, a minimum requirement was set with 290 x 300 mm stage size in the Purchase Request.
Inclusions: 5. with inclusion of freebies	Inclusion of additional items: UPS and Printer: Printer specification: - w/ wireless solution plus Ethernet - easy iPad, iPhone, Android tablet and smartphone printing; includes Wi-Fi Direct for network-free printing and NFD touch-to-print capability - easy setup and navigation - 2.7" color touchscreen to easily print, copy, scan and fax - reload paper less often - 150 sheet paper capacity - Efficient - save time and paper with auto 2-sided printing; plus, a 30-page Auto Document Feeder for copying and scanning - Nozzle Configuration: 400 nozzles black, 128 nozzles each color - print speed: 13.7 ISO ppm (black), 7.3 ISO ppm (colored) UPS: - Output Power Capacity: 550 Watts/1100 VA - Max Configurable Power: 550 Watts/1100 VA - Nominal Output Voltage: 230 V - Output Connections: (2) IEC 320 C13 (Battery Backup) - Nominal Input Voltage: 230 V
Objectives: CFI Plan Fluor DL 4X F N.A. 0.13, W.D. 16.4mm, PhL CFI Plan Fluor DL 10X A N.A. 0.30, W.D. 15.2mm, PhL-1 CFI Super Plan Fluor ELWD ADM CFI Super Plan Fluor ELWD ADM	"CFI" brand specification be removed but suppliers could offer with different brand, same specification

Camera System:	"DS Ri-2" brand specification be removed but suppliers coul offer with different brand, same specification	
Microscope camera w/ 16.25	one manufacture of the second	
million pixels, DS Ri-2		
Microscope Camera		
Epi-Flourescence Attachment:	"Intensiligth C-HGFI" brand specification be removed but	
Precentered Fiber Illuminator INTENSILIGTH C-HGFI	suppliers could offer with different brand, same specification	
INTENSILIGITA C-HGFI	End-User note: Minimum requirements are set in the	
LED Lamphouse: For Dia	specification to optimize use for research and advancement	
Illumination equipped w/ ND32	Mercury Lamp is preferred over LED as it is used in reflected	
Filter x 1 cable will be connected to	illumination or flourescence application and bright field	
LAMP CTRL	application. Mercury Lamp also generates less heat as	
Lamp, HG Fiber, DAPI Filter Cube,	compared to LED, thereby extending the viability of samples for	
	examination.	
ITB #2019-022 Supply and Delivery	,	
1 unit Pick-up, 4x4, 2.8L diese	l,	
manual transmission	All and Continue at I and the continue at I	
Dimension & weight:	All specifications : at least minimum requirements, a little	
Overall dimension (mm): 5,335 x 1,855 x 1,815	lower or higher, manufacturers' specifications	
Engine	2.8L is the minimum requirement	
Engine type: 2.8L Diesel, 4 cylinder,	2.02 to the minimum requirement	
16-valve		
Γransmission:	at least minimum requirements, a little lower or higher	
Tires: 265 / 65	manufacturers' specifications	
Wheels (size): R17 steel		
gate, installation of wheel bath w/r	Materials for the Repair/Renovation of Bio- Security House, oofing poly carbonate siding, construction of 45.00m rainting of existing bio-security fence 84 columns/bays areas at NSPRDC, Tiaong, Quezon.	
Queries on the detailed Scope of	End User and TWG shall respond to other queries in	
Works and measurements, etc.	necessary. Prospective Bidders encouraged to conduct actual	
	project site inspection and assessment	
Please be guided accordingly.		
Blaharor		

LAARNI Z. CABANTAC, DVM Vice-Chair, Bids and Awards Committee

Received by the Bidder/Representative:	
Date :	