



August 8, 2022

Date

REQUEST FOR QUOTATION SMALL VALUE PROCUREMENT

INSTRUCTION:

1. Bidders are required to read the instructions and fill all the blanks properly, Prospective Bidders/Suppliers are required to use this official canvass form in accomplishing their bid proposals/quotation.
2. Any specifications other than those required/stated in this form shall not be considered in their evaluation of bid.
3. Quotation must be the lowest price(s), taxes included for the item(s) services listed hereunder including delivery charges.
4. Always indicate the brand name of the offered items (s) or product.
5. Price quotation(s) submitted shall be valid for ONE HUNDRED TWENTY DAYS (120) days reckoned from the deadline for submission of quotations.
6. Terms of payment-Thirty (30) days from delivery of items(s)
7. **Only sealed quotations shall be considered by BAC. The Bidders/Suppliers or Authorized Representative shall indicate on the envelope the RFQ Number and the company name of the bidder/supplier.**
8. Awarding shall be done by **LOT /CATEGORY** only.
9. Delivery and/or Installation Period: 30 working days upon receipt of Notice to Proceed

ADMIN DEADLINE FOR SUBMISSION OF BIDS
2022-08-

August 11, 2022

4:00 PM

Date

Time

PR No. 194 End-user: MARITES C. GEALONE ABC:

Qty.	Unit	Item/Description	ABC (Php)	Offered brand	Unit price	Total cost
1	lot	Smart-UPS (Rack Mount)	500,000.00			
		1 unit-Smart-UPS 5000VA (Rack mount)				
		Output: Output power capacity 4.5kwatts/5.0kVA, Max Configurable Power (Watts) 4.5kWatts/5.0kVA, Nominal Output Voltage 230V, Output Voltage Distortion less than 2%, Output Frequency (sync to mains) 50/60 Hz +/- 3 z Sync to mains, Other Output, Voltages 220- V, 240 V, load Crest Factor 3:1, Topology Double conversion online, Waveform type Sine wave, Output Connections (4) IEC 60320 C19, (2) IEC Jumpers, (6) IEC 60320 C13, Bypass Internal bypass (automatic and manual)				
		Input: Nominal Input Voltage 230V, Input frequency 40 -, 70Hz Auto-sensing, Input Connections Hard wire 3-wire (1P + N + E), Input voltage range for main operations, 100-275 Adjustable (half load), 160-275V, Other Input Voltages 220 V, 240V				
		Batteries & Runtime: Included Battery Modules 2, Typical recharge time 1.5 hour(s), Nminal Battery Voltage 192 V Replacement Battery APCRBC140, Expected Battery Life (years)5, RBC Quantity 1, Battery Charge Power (Watts) 560 watts.				
		Conformance: Approvals CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, IRAM, RCM, VDE Standard warranty 3 yaers repair or replace (excluding batter) and 2 years for battery				
		1 unit Smart-UPS 3000VA (Rack Mount)				
		Output: Harmonic distortion less than 5%, Maximum configurable power in VA 3000 VA, Maximum configurable power in W 2100 W, Transfer time 8 ms typical: 10 ms maximum UPS type Line interactive Wave type Sine wave, Output frequency 50 Hz sync to main				
		Input: Input voltage limits 180...287 V, Network frequency 50/60 Hz +/- 3Hz auto-sensing				
		Surge Protection and Filtering: Surge energy rate 300J, Noise suppression Full time multi-pole noise filtering: 0.3%, IEEE surge let-through: zero clamping response time: meets UL 1449				
		Batteries & Runtime: Extended runtime 0, Number of battery filled slots 0, Number of battery free slots, battery recharge time 3 h, Number of battery replacement quantity 1, Battery life 3 ...5 year (s) Battery power in VAH 490 Vah runtime, Battery charger power 163 W rated				
		2 years warranty				
		1 unit Smart-UPS 2200VA (Rack Mount)				
		Output: Maximum configurable power in W 1980 W harmonic distortion less than 2%, Output frequency 50/60 Hz +/- 3 Hz sync to mains Crest factor 3: 1 UPS type Double conversion online Wave type Sine wave Bypass type internal bypass (automatic and manual)Maximum configurable power in VA 200 V				
		Input: Network frequency 40 ...,70 Hz auto-sensing input voltage limits 100 ...275 V adjustable (half load)				
		Batteries & runtime: Number of battery filled slots 1 Number of battery free slots 0, Battery recharge time 3 h,Number of battery replacement quantity 1 Additional information Configurable for 220:230 or 240 nominal output voltage Battery voltage 72 V, Battery charger power 122 W rated, Battery power in VAH 367 VAH runtime, Battery life 3 ...5 year (s)				

LOLITA M. JUMALON

G-EPS Posted

PAUL C. LIMSON, DVM

Chair, Bids and Awards Committee

CANVASSER'S CERTIFICATION

This is to certify that I have full knowledge, authority and responsibility in distributing and/or collecting the Request for Quotation in accordance to the guidelines in securing prices for the Bureau of Animal Industry.

(Signature Over Printed Name)
Authorized Canvasser

The BAI Bids and Awards Committee (BAC)
Visayas Awanue, Diliman, Quezon City

Sir/Madam:

In connection with the above request, I/We hereby submit our quotation indicated above. I/We have carefully read and fully understand the minimum requirements and agree to furnish and/or effect delivery in conformity with specifications any or all said articles/services described above within _____ working days from receipt of Purchase Order.

_____ Signature Over Printed Name	_____ Name of Company	_____ Tax Identification Number
_____ Telephone Number(s)	_____ Address	(To be filled by Supplier) _____ Date accomplished

Mandatory Requirements for submission:	
✓ Mayor's Permit (Updated)	✓ Income Tax Return (for ABCs above P500k)
✓ PhilGEPS Registration/Certificate (Updated)	✓ Omnibus Sworn Statement (For ABCs above P50K) (Unnotarized OSS may be submitted provided that the notarized OSS shall be submitted prior to issuance of Notice of Award.